

03-01-00

A

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)
 Approved for use through 09/30/2000. OMB 0651-0032
 Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
 Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. RAL97-0043US2

First Inventor or Application Identifier Doidge, D. et al

Title Method and Apparatus for Forwarding...

Express Mail Label No. EK313649251US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 48]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 12]
4. Oath or Declaration [Total Pages 3]
 - a. ☐ Newly executed (original or copy)
 - b. ☒ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

ADDRESS TO: Assistant Commissioner for Patents
 Box Patent Application
 Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement of Power of Attorney
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☒ Information Disclosure Statement (IDS)/PTO-1449 [Copies of IDS Citations]
11. ☒ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity Statement filed in prior application, Status still proper and desired
(PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other: _____

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☒ Divisional ☐ Continuation-in-part (CIP) of prior application No. 08 / 956,077

Prior application information: Examiner D. Ho Group / Art Unit. 2738

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

Name	Daniel E. McConnell				
	IBM Corporation				
Address	Intellectual Property Dept. 2Y7/B656				
	P. O. Box 12195				
City	RTP,	State	NC	Zip Code	27709
Country	USA	Telephone	919-543-1105	Fax	919-543-3634

Name (Print/Type)	Daniel E. McConnell	Registration No. (Attorney/Agent)	20,360
Signature	<i>Daniel E. McConnell</i>	Date	29 Feb 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

 02/29/00
 1c685 U.S. PTO

 1c525 U.S. PTO
 09/515746

02/29/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: D. A. Doidge

Serial No.: 08/956,077

Group Art Unit: 2738

Filed: Concurrently Herewith

Examiner: D. Ho

For: Method and Apparatus for Hardware Forwarding of LAN Frames over ATM Networks

Assistant Commissioner for Patents
Washington, D.C. 20231

EXPRESS MAIL CERTIFICATE

"Express Mail" label number: __EK313649251US__

Date of Deposit: __Feb. 29, 2000__

I hereby certify that the following **attached** paper or fee

1. Application under CFR 1.53 (b) (Divisional) with Preliminary Amendment
2. Utility Patent Application Transmittal form and Fee Transmittal
3. Copy of Patent Application as originally filed
4. Copy of Declaration and Power of Attorney as originally fixed
5. IDS and PTO 1449, copies of cited references
6. Drawings - 12 sheets
7. Reply Post Card

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to:

BOX Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

__Saundra S. Christopher__
(Name of person mailing paper or fee)

Saundra S. Christopher
(Signature of person mailing paper or fee)

EXPRESS MAIL LABEL NO.: EK313649251US

DATE OF DEPOSIT: Feb. 29, 2000

I hereby certify that this paper and fee are being deposited with the United States Postal Service Express Mail Post Office to Addressee service under 37 CFR §1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents, Washington, D.C. 20231.

Saundra S. Christopher
NAME OF PERSON MAILING PAPER AND FEE

Saundra S. Christopher
SIGNATURE OF PERSON MAILING PAPER AND FEE

In the United States Patent and Trademark Office

Date: Feb. 29, 2000

In re Application of: Doidge, D. et al

Filed:

For: Method and Apparatus for Hardware Forwarding of LAN Frames
Over ATM Networks

Serial Number: 08/956,077

Art Unit: 2738

Examiner: D. Ho

PRELIMINARY AMENDMENT FILED WITH A DIVISIONAL APPLICATION
UNDER 37 CFR 1.53(b)

Hon. Commissioner of Patents and Trademarks
Washington, DC 20231

Sir:

This Preliminary Amendment is filed with a Divisional Application under 37 CFR
153(b).

This patent application is a Divisional of patent application serial no. 08/956,077, filed
October 22, 1997, US Patent No. _____.


In the Claims:

Please cancel the claims 1, 4-21.

REMARKS

This is a Preliminary Amendment filed with the Divisional Application under 37 CFR 1.53
(b). Claims 2-3, 22-33 are presented for examination. The Examiner is urged to call the undersigned at the below-listed telephone number if, in the Examiner's opinion, such a phone conference would expedite or aid in the prosecution of this application.

Respectfully Submitted,



Daniel E. McConnell,
Reg. No. 20,360
Attorney of Record

Telephone: 919-543-1105
FAX: 919-543-3634

**METHOD AND APPARATUS FOR HARDWARE
FORWARDING OF LAN FRAMES OVER ATM NETWORKS**

BACKGROUND OF THE INVENTION

5

Technical Field of the Invention

10

The present invention relates to local area network switching apparatuses for routing and bridging data transfers to other networks of a different type. The invention further relates to transferring messages between networks having non-compatible network interfaces and different data link protocols. The disclosed system relates to bridging between networks using special-purpose hardware.

15

Background Art

20

25

Presently, numerous types of networks coexist in the telecommunication industry, such as Local Area Networks (LANs), Wide Area Networks (WANs), X.25 Networks, Integrated Services Digital Networks (ISDNs), and Asynchronous Transfer Mode (ATM) Networks. Because of the existence of different networks and standards, there is a need in the telecommunications industry for communication between data processing devices connected to heterogeneous networks. As an example, owners of previously installed LANs frequently want to connect to the emerging broad band Integrated Services Digital Network (ISDN) or ATM Networks.

PATENT APPLICATION

In a worldwide effort to harmonize the development of networks and the data processing devices associated with them, international organizations like the Comite Consultatif International de Telegraphe et Telephone (CCITT), the European Computer Manufacturers' Association (ECMA), and the International Organization for Standardization (ISO) have established standards for each type of network. ISO has developed a general framework to serve as a reference for all existing and future standards, called the reference model of Open Systems Interconnection (OSI). Most existing and newly developed standards claim to be OSI compatible. This model is a universally applicable logic structure or layered architecture, containing seven layers as shown in FIG. 1. Each layer has a set of defined functions and provides a set of services to and from the adjacent two layers.

LAN switches are widely used by industry to interconnect multiple Ethernet or Token Ring LANs through a switch so that devices on one LAN can communicate with devices on other LANs. New LAN switches are being developed to interconnect networks having various data link (layer 2) protocols to enable various LAN segments to connect to ISDN or ATM networks. This merging technology requires a format conversion between the different protocols used on the networks.

Much prior art has dealt with the format conversion of one network protocol to another. In U.S. Patent 5,341,376, "An ATM Cell Format Conversion System," Yamashita teaches an ATM cell format conversion system. ATM means Asynchronous Transfer Mode, which is the current popular method for transmitting speech, data,

PATENT APPLICATION

and pictures over the Internet. An ATM cell is the basic unit in which data is transmitted. An ATM cell is comprised of 53 octets of data, where an octet is another term for byte or eight bits of data. The 53 octets are subdivided into five octets for carrying header information for the message being transmitted including the message destination and 48 octets for carrying message data. A message is segmented into ATM cells as it is sent to the Internet and then reassembled from ATM cells at the destination.

Yamashita has found that when transmitting messages formatted into 53 ATM octets over telephone lines using older techniques, such as Synchronous Transfer Mode (STM), the standard ATM format is not totally compatible. For STM, Yamashita found that better efficiency can be attained for transmitting ATM cells over STM media by adding an idle (dummy) octet to each ATM cell and thus comprising an ATM cell of 54 octets rather than 53. Yamashita teaches an ATM cell format conversion system to generate 54 octet cells from 53 octets cells. Like Yamashita, the present invention uses ATM transmissions, but Yamashita does not use the standard ATM format. Yamashita converts the basic ATM format of transmission from 53 to 54 octets. This makes Yamashita's ATM non-standard and not used by the rest of the industry. The present invention uses the standard ATM solution having 53 octets, never attempts to modify the standard approach, and does not use Yamashita's invention.

In U.S. Patent 5,323,392, "Adaption Device and Method for Efficient Interconnection of Data Processing Devices and Networks" by Ishii et al., Ishii teaches an adaption device for connecting

PATENT APPLICATION

processing devices and networks which have different protocols. Ishii's adaption device for connecting processing devices and networks which have various layer 2 (link layer) protocols of the HDLC (High Level Data Link Control) type. HDLC is the standard
5 used most commonly for layer 2.

Ishii's adaption device interconnects two different protocols of the HDLC generic type: 1) Link Access Procedure on the D Channel (LAPD), which is Link Access Procedure Balanced (LAPB),
10 which is specific to LANs. An HDLC frame, incoming from a first data processing device complying to the first layer 2 protocol of the LAPB type, is stored within the adaption device. The frame is then mapped to a second layer 2 protocol of the LAPD type and forwarded to a network interface. The layer 2 mapping function resides in a Programmable Read-Only Memory (PROM), a receive frame is stored in adapter memory, and the mapping function between layer 2 protocols is done by a microprocessor.
15

The present invention, like Ishii, features methods for adapting different layer 2 protocols. The present invention maps switch header to ATM control header but uses hardware rather than a processor to do the mapping function. Ishii's solution is related to slower network transfer rates where slower microprocessor controlled mapping is permissible. The present
20 invention is for higher speed networks where Ishii's processing mapping speeds are not acceptable.
25

In U.S. Patent 5,581,558, "Apparatus for Bridging Non-Compatible Network Architectures" by Horney et al, Horney

PATENT APPLICATION

teaches a bridging apparatus for sending data to and from a local area network (LAN) from and to a wide area network (WAN). Horney's invention also deals with the OSI model of layered protocols of FIG. 1 and with various layer 2 protocols. Horney chooses a popular wide area network standard called X.25, which is based on the Comite Consultatif International de Telegraphe et Telephone (CCITT) definition of the lower three layers of the OSI model. Horney converts the X.25 protocol to a 1Mb (StarLAN) local area network, which is an IEEE 802.3 Carrier Sense multiple Access with Collision Detection ((CSMA/CD) LAN protocol. The layer 2 mapping function resides in a Read-Only Memory (ROM), a receive frame is stored in adapter memory, and the mapping function between layer 2 protocols is done by a microprocessor.

Both Horney and the present invention feature methods for bridging data between different layer 2 protocols. However, the present invention maps switch header to ATM control header but uses hardware rather than a processor to do the mapping function. Horney's solution is related to slower network transfer rates (56 Kbits/sec) where slower microprocessor mapping is permissible. The present invention is for higher speed (155 Mbits/sec) networks where processing mapping speeds are not acceptable.

In U.S. Patent 5,577,039, "System and Method of Signal Transmission within a Plesiochronous Digital Hierarchy Unit Using ATM Adaption Layers" by Won et al., Won teaches a format conversion system for converting the plesiochronous digital hierarchy (PDH) data transmission format to the ATM data transmission format and for converting ATM to PHD. PHD is a scheme for multiplexing

PATENT APPLICATION

several 64Kbit/sec ISDN channels together to produce a higher bit rate signal. Like the other prior art solutions, Won uses memory and a microprocessor in the conversion system to perform the mapping functions between the two protocols being converted. The present invention neither maps PDH to ISDN nor uses microprocessor control in bridging between networks.

In U.S. Patent 5,619,650, "Network Processor for Transforming a Message Transported from an I/O Channel to a Network by Adding a Message Identifier and then Converting the Message" by Bach et al, Bach teaches converting an I/O Channel format to a LAN format. Bach's invention for the most part is not related to the present invention. Both Bach and the present invention feature methods for adapting two dissimilar interfaces; however, the present invention maps switch header to ATM control header but uses hardware rather than a processor to do the mapping function. Bach maps a standard I/O Channel to a LAN using a processor.

In U.S. Patent 5,568,477, "Multipurpose Packet Switching Node for a Data Communication Network" by Galand et al., Galand teaches a multi-purpose packet switching network node capable of switching packets received on any number of node input ports to any number of output ports. The node can receive either ATM cells or variable length messages on any input and switch that input to any switch output of the node. Reformatting is involved of both ATM or variable length (VL) messages to a packet format, which is basically comprised of pseudo ATM packets that carry segmented VL data.

PATENT APPLICATION

Both Galand and the present invention feature methods for adapting a protocol to the ATM cell format and both apply to switches. However, Galand's solution adapts a variable length message, like that used for a circuit switch, to the ATM cell format using a microprocessor and defines a switch that switches ATM cells. The present invention uses a switch that switches LAN frames and not ATM cells.

The present invention also teaches an increased throughput capability between networks. Prior art includes U.S. Patent 5,457,681, "ATM-Ethernet Portal/Concentrator" by Gaddis et al. Gaddis teaches an Ethernet to ATM converter. Gaddis expands the distance an Ethernet segment (which is a LAN) can transmit a message by connecting the Ethernet segment to an ATM Network. In fact, Gaddis connects multiple Ethernet segments to a multi-ported ATM Network, whereby he enables a first Ethernet segment to send messages to a second Ethernet segment through the ATM Network. Gaddis features a dual-ported memory with the ATM input and output controlled by a DMA controller and the Ethernet input and output controller by an Ethernet controller. A processor is required to control and program both the DMA and Ethernet controllers. Messages from either source are stored in the dual-ported memory depending on which direction the message is traveling. Both Ethernet and ATM headers are generated directly from the memory with the help of the controllers. This method also enables message broadcast to occur from the dual-ported memory, thus eliminating a need to copy the data from an external memory if the message is broadcast.

PATENT APPLICATION

Gaddis claims the invention to be used as either a portal or a concentrator, where a portal connects one Ethernet segment to one port of an ATM network and a concentrator connects multiple Ethernet segments to one ATM network. For the concentrator, a bus is used to interconnect the multiple Ethernet segments, and the bus goes to one port of the dual-ported memory. The bus becomes a bottleneck for the concentrator, and the performance is questionable and depends upon improving the performance of the bus.

Both Gaddis and the present invention feature methods for connecting LANs to ATM networks and for converting messages in LAN formats to messages in ATM format. The present invention only deals with a switching approach for interconnecting multiple LANs to multiple ATM ports. Multiple connections are supported simultaneously through the LAN port switch. The present invention is neither a single portal approach nor a concentrator. Gaddis's invention functions as a portal or a concentrator and does two basic operations: 1) converts Ethernet messages to ATM messages and 2) converts ATM messages to Ethernet messages. In contrast, the present invention is for a LAN switch or hub which either bridges or routes LAN messages or ATM messages. The present invention also performs LAN emulation and supports virtual LANs. Gaddis uses software control by a processor, and the present invention is more efficient using an all hardware solution.

In U.S. Patent 5,303,344, "Protocol Processing Apparatus for use in Interfacing Network Connected Computer Systems Utilizing Separate Paths for Control Information and Data Transfer" by Yokoyama et al., Yokoyama teaches a communication control equipment

PATENT APPLICATION

connected between a computer and a network to expedite the sending and receiving of messages. The control of the complete message prior to Yokoyama's invention was accomplished by the software of the computer only. A communication control equipment is introduced as new hardware to take the some of the processing burden off of the computer. The computer still does some of the message control, and some is off-loaded to the new hardware. The invention takes mainly a parallel processing approach in that the communication control equipment is comprised of multiple processors, each of which relieve the computer of one of the message control tasks.

There is a similarity between Yokoyama and the present invention in that both use additional hardware to improve the speed of processing messages. Another slight similarity is that Yokoyama splits a single message into two different processing paths internal to his additional hardware. Likewise, the present invention uses two different processing paths. However, Yokoyama uses multiprocessors in his new hardware to improve the performance of messages, where the present invention uses special-purpose hardware to further improve performance. The present invention is better, because general purpose processors cannot handle a specific task as quickly as special hardware can.

Yokoyama splits a single message into two paths sending control information down one path and data down the other. The present invention segregates different types of messages by path, sending bridged messages requiring layer 2 conversions down one path in their entirety and routed messages requiring layer 3 conversions down a second path in their entirety. In addition,

PATENT APPLICATION

Yokoyama deals with the scenario of a plurality of computers connected to a network. Communication between computers uses a single homogeneous message protocol, where all messages are comprised of the exact same protocol and format. The protocol includes a complex control structure, wherein first a sequence of messages is used to establish a connection through the network by the computer requesting a specific connection, the network establishing the connection path and sending an acknowledge message back to the computer. Next, the computer sends data over the established connection, wherein a single or multiple messages can be transferred. When the computer is finished using the connection, it then sends a message to break the connection. In contrast, the present invention deals with a switch hub scenario which receives heterogeneous messages of various protocols from local area networks (LANs) and Asynchronous Transfer Mode (ATM) messages. The heterogeneous messages are either routed by the switch hub or bridged from one hub input port to another hub output port. The present invention therefore deals with multiple different message protocols and converts a first message protocol to a second message protocol using special purpose hardware (no processor) to expedite the conversion.

Other prior art which is not as closely related is disclosed in the article, "High-Speed Serial Interface MicroChannel Adapter", in the *IBM Technical Disclosure Bulletin*, Vol. 34, No. 7A, December 1991. The article discloses a High-Speed Serial Interface (HSSI) for transferring data at 52 Mbit/sec using a pseudo standard which was jointly developed by T3plus Networking and Cisco Systems. The disclosure is of an apparatus for connecting the MicroChannel bus

to the HSSI interface. Both the *IBM Technical Disclosure Bulletin* (TDB) and the present invention feature methods for adapting two dissimilar interfaces. However, the *IBM TDB* deals with connecting a computer bus to a serial interface, not with interconnecting multiple networks through a switch.

It is the object of this invention to sort incoming LAN messages at each ATM port of the switch into two different paths for efficient routing or bridging between dissimilar networks.

It is a further object of this invention to provide a high performance bridging path between dissimilar networks by implementing the bridging path as a hardware forwarding engine for transmitting LAN frames between LAN ports and ATM ports of the LAN switch.

It is a further object of this invention to provide LAN emulation over ATM networks which permits LAN frames to be transmitted between two different LAN segments interconnected by an ATM network.

It is a further object of this invention to convert formats between different layer 2 protocols using special purpose hardware without the aid of a microprocessor.

It is a further object of this invention to provide two different types of memory queues, one being a software queue of frames to be processed by a microprocessor and the other being a

PATENT APPLICATION

hardware queue of frames to be processed by a hardware forwarding engine.

RA9-97-043

SUMMARY OF THE INVENTION

In accordance with the invention, a LAN switch is provided for bridging messages in the form of LAN frames between LAN segments and ATM networks. A plurality of LAN switch ports are a mix of LAN ports and ATM ports for transmitting messages to and from LAN segments and to and from ATM network. Format conversion is required at the ATM ports between the incompatible OSI layer 2 and 3 protocols of the LAN frames and the ATM network.

For transmitting LAN frames from a LAN port to an ATM port, the ATM port sorts the incoming messages arriving from the LAN port through the switch to the ATM port. The ATM ports sort incoming LAN messages to determine if they are to be discarded, sent to another LAN, routed, or bridged. The route verses bridge decision is based on whether layer 3 conversion is required or not. LAN frames requiring layer 3 conversion are called routed frames, and LAN frames not requiring layer 3 conversion are called bridged frames.

Bridged frames require only layer 2 data link protocol conversion, and special-purpose hardware means are provided to convert the arriving LAN frame having a switch header prefix. The switch header is removed and replaced by ATM control device header. The LAN frame prefixed with the ATM control header is sent to an ATM controller device. The ATM controller device is an Application Specific Integrated Circuit (ASIC) which segments/reassembles ATM cells for transmission to and from the ATM network. The ATM controller device header is in a form that is understood by the ATM

PATENT APPLICATION

controller device, and no other conversion is required by the special-purpose hardware.

5 In further accordance with the invention, a LAN emulation means is provided for transmitting and receiving LAN frames from one LAN segment to a port of a first LAN switch, through the LAN switch to a first destination ATM switch port, converting to ATM cell format, transmitting the frame over the ATM network to a second ATM port of a second LAN switch, reassembling the LAN frame, 10 and sending the reconstructed LAN frame to a second LAN segment connected to a LAN port of the second switch. The ATM network then appears to emulate a LAN, since a LAN frame travels intact from the first LAN segment through the ATM to a second LAN segment. The LAN frame arriving at the second LAN segment appears as if first and second segments were connected directly through a LAN switch and had never undergone conversion to the ATM format. The LAN emulation is provided by a LAN emulation header, which is sent with the LAN frame over the ATM network to carry information that is required to reconstruct the LAN frame after exiting the ATM 20 network.

Other features and advantages of this invention will become apparent from the following detailed description of the presently preferred embodiment of the invention, taken in conjunction with 25 the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram showing the reference model of the Open Systems Interconnection (OSI) organization comprised of a universally applicable layered architecture, containing seven layers according to the prior art.

FIG. 2 is a diagram showing the interconnection of LANs to the ATM network using LAN switches according to the preferred embodiment of this invention.

FIG. 3 shows a block diagram of the LAN switch comprising LAN ports and ATM ports according to the preferred embodiment of this invention.

FIG. 4 shows a block diagram of the ATM port for converting LAN frames to ATM frames according to the preferred embodiment of this invention.

FIG. 5 is a flow chart of the operation for transmitting and converting a LAN frame to the ATM network according to the preferred embodiment of this invention.

FIG. 6 is a diagram showing the composition of the switch header for transmitting a LAN frame through a LAN switch according to the preferred embodiment of this invention.

PATENT APPLICATION

FIG. 7 is a block diagram showing the sorting of incoming LAN frames into bridged frames and routed frames according to the preferred embodiment of this invention.

FIG. 8 is a block diagram showing the hardware format conversion of LAN frames to ATM frames according to the preferred embodiment of this invention.

FIG. 9 is a diagram showing the composition of the ATM control header for prefixing an ATM frame for transmission to the ATM interface adapter according to the preferred embodiment of this invention.

Fig. 10A is a block diagram of the ATM adapter for the segmenting/reassembling of ATM frames to and from ATM cells according to the preferred embodiment of this invention.

FIG. 10B is a diagram showing the basic composition of the ATM cell for transmission to and from the ATM network according to the preferred embodiment of this invention.

FIG. 11 is a flow chart of the operation for transmitting and converting an ATM frame from the ATM network to the LAN according to the preferred embodiment of this invention.

FIG. 12 is a block diagram showing the redirecting and classifying of incoming ATM frames into bridged frames and routed frames according to the preferred embodiment of this invention.

PATENT APPLICATION

FIG. 13 is a block diagram showing the hardware format conversion of ATM frames to LAN frames according to the preferred embodiment of this invention.

5 FIG. 14 is a diagram showing the composition of the logical port conversion word, which is stored in look-up tables in frame memory according to the preferred embodiment of this invention.

10 FIG. 15 is a block diagram showing the detection of LAN emulation control frames according to the preferred embodiment of this invention.

FIG. 13 is a block diagram showing the hardware format conversion of ATM frames to LAN frames according to the preferred embodiment of this invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In accordance with the invention, a LAN switch is provided for bridging messages in the form of LAN frames between LAN segments and ATM networks. A plurality of LAN switch ports are a mix of LAN ports and ATM ports for transmitting messages to and from LAN segments and to and from ATM networks. The preferred embodiment is a plurality of LAN ports being switched to connect to each other and to one ATM port.

Referring to FIG. 1 (prior art), the present invention is compatible with the communication standard provided by the reference model of the Open Systems Interconnection (OSI). This model is a universally applicable logic structure or layered architecture, containing seven layers as shown in FIG. 1.

Each layer has a set of defined functions and provides a set of services to and from the adjacent two layers. The present invention applies to two of the lower layers, layers 2 and 3. The layer 1 physical connections are well defined and unchangeable. Layer 1 includes physical connectors, wiring, and transmission sequences.

The invention applies mainly to layer 2, the data link layer, and to layer 3, the network layer. Format conversion is required at the ATM ports between the incompatible OSI layers 2 and 3 protocols of the LAN frames and the ATM network.

PATENT APPLICATION

Referring to FIG. 2, the preferred embodiment is shown. A plurality of LAN switches 20 interconnect multiple LAN segments 30 with an ATM network 25. The LAN switch in the prior art interconnected a plurality of LAN segments, such as a plurality of computer terminals, personal computers, or workstations within an office building, wherein each segment connecting the computer terminals, personal computers, or workstations was located on a different floor of the building. The LAN switch interconnects all floors to enable the transmission of data messages configured as LAN frames between floors. The present invention adds ATM ports and an efficient hardware format conversion and forwarding engine to the prior art LAN switch, making it possible to interconnect multiple LAN segments 30 that are connected to different LAN switches 20 via ATM network 25.

For instance, LAN segment A can connect to LAN segments B, C internal to LAN switch A. However, LAN segment A can also connect to ATM network 25 through link 40 and form a virtual channel connection across ATM network 25 to connect to LAN switches B or C. Thus, LAN A can be connected to LANs D to K across the wide area ATM network 25. As a data message is transmitted across the ATM network, the message maintains the LAN frame format even though the frame is segmented into ATM cells at the ATM port of LAN switch 20 for transmission across the ATM network 25 and then reassembled into a LAN frame at the ATM port of the LAN switch 20 on the other side of the ATM network.

ATM network 25, although not a LAN itself, emulates a LAN and makes it appear like LAN A is connected to LAN K (for instance)

through a local LAN switch 20 when, in reality, LANs A and K can be very far apart as ATM network 25 is very flexible (like telephone lines) and can connect two LANs in the same building, town, country, or world. The ability to support LAN frame traffic between LAN segments by traversing over an ATM network is referred to as a virtual LAN system, since the operation at the end point is consistent with normal LAN operation but the ATM network interconnecting the LANs is itself not a LAN. Thus, the present invention permits local area networks to expand their range to include interconnection to any LAN connected to ATM network 25 and to transfer data at the highest possible rate.

Referring to FIG. 3, the preferred implementation of LAN switch 20 has, for example, three LAN ports 50 and one ATM port 60. Ports 50, 60 are interconnected by switch 70 such that any of the LAN ports 50 can be switched to connect to any other LAN Port 50 or ATM port 60. Likewise, ATM port 60 can be switched to connect to any LAN Port 50. Switch 70 is capable of supporting multiple connections simultaneously and is bi-directional. The interface to and from switch 70 is bi-directional switch bus 52. The interface to each port 50, 60 is switch bus 52 regardless of the port type or number of ports supported by switch 70.

The present invention is for special-purpose hardware residing in ATM port 60 of LAN switch 20 for expediently handling format conversion and frame forwarding between two dissimilar networks. The invention incorporates dual hardware functions, one for converting LAN/switch frame formats to ATM frame formats and one for converting ATM frame formats to LAN/switch frame formats.

PATENT APPLICATION

Referring to FIG. 4, a block diagram of the special-purpose hardware is shown. The special hardware for converting LAN/switch frame formats to ATM frame formats includes LAN frame sorting logic 80 for receiving and sorting LAN frames received from switch 70 (shown in Figure 3) over switch bus 52. The LAN frames are sorted for either software or hardware processing. The frames to be processed by hardware are stored in hardware queue 102 of frame memory 100, and the frames to be processed by software are stored in software transmit queue 104 of frame memory 100. LAN frames queued for software processing in software transmit queue 104 are sent to routing processor 130 to be processed. LAN frames queued for hardware processing in hardware transmit queue 102 are sent to switch-to-ATM header conversion logic 85 to be processed. Switch-to-ATM header conversion logic 85 converts from the LAN frame format coming from the switch to the emulated LAN frame format required by the ATM adapter 120. The ATM adapter 120 contains an ATM controller ASIC for converting to and from an ATM transmission form. The standard ATM transmission format is the ATM cell. The ATM cell is comprised of 53 octets of data, where an octet is another term for byte or eight bits of data. The 53 octets are subdivided into five octets for carrying header information including the channel to be used for transmission through the ATM network and 48 octets for carrying message data. A message is segmented and transmitted across ATM network 25. On the other side of the network, the cells are received and reassembled from ATM cells at the destination. ATM adapter 120 performs both the transmission and receiving functions; i.e., block 120 segments out-going messages and reassembles incoming messages.

PATENT APPLICATION

The special hardware for converting ATM frame formats to LAN/switch frame formats includes ATM frame classification block 90 for receiving a LAN frame that has been reassembled from ATM cells into ATM frame format by ATM adapter 120. ATM frame classification block 90 sorts the ATM frames for either software or hardware processing. The frames to be processed by hardware are stored in hardware receive queue 202 of frame memory 100, and the frames to be processed by software are stored in software receive queue 204 of frame memory 100. Frames queued for software processing in software receive queue 204 are sent to routing processor 130 to be processed. Frames queued for hardware processing in hardware receive queue 202 are sent to ATM-to-switch header conversion logic 95 to be processed. ATM-to-switch header conversion logic 95 converts from the ATM frame format to the LAN format required by switch 70. The frame converted back to a LAN frame is sent through switch 70 over switch bus 52 and routed to one or more of the LAN ports 50 of LAN switch 20.

The hardware conversion of frames in both hardware queues 102, 202 require look-up table operations to perform the specified format conversions. For the preferred embodiment, the conversion tables 110 are stored in frame memory 100. For other embodiments, all or some of these tables are stored in discrete memories. The detailed use of conversion tables 110 is explained hereinafter.

Transmitting LAN frames to ATM

Referring to FIG. 5, a flow diagram is shown of the transmit operation. For transmitting LAN frames from LAN port 50 to an ATM port 60, the LAN frame first arrives from a LAN 30 to a LAN port 50 (see FIG. 3) as shown by block 200. The LAN port 50 applies the MAC address portion of the LAN frame to perform a look-up for conversion tables 110 to determine what action is to be taken with the LAN frame, as shown in block 202. MAC stands for Media Access Control, which is the bottom sublayer of the data link layer 2 (see FIG. 1). LAN port 50 makes a decision to determine if the frame is to be discarded, sent to another LAN, or sent to ATM port 60, as shown in block 204. The decision to discard or send to another LAN port 50 is shown in block 206. Note that this path is not pertinent to the present invention and its flow is not followed in FIG. 5. The path of interest is shown by block 208, where the LAN frame destination is ATM port 60. In this case a switch header is prefixed to the LAN frame by the LAN port 50. The LAN frame with switch header attached is the LAN/switch frame 188; i.e., the LAN frame that is sent through switch 70.

Referring to FIG. 6, the content of the switch header 180 is shown. Switch header 180 is comprised of two 32-bits words for defining tag field 182, frame type field 184, and exit port field 186. Tag field 182 contains a binary address to be applied to conversion table 110 for looking up control data in the tables 110 to aid in the hardware conversion of the LAN/switch frame 187 to the ATM frame 288. Type field 184 contains information about the

type of frame, such as abort frame, CRC is included in frame, and other control descriptors. Exit port field 186 determines which port 50 or 60 the LAN/switch frame is sent to through switch 70. Each of the 32 bits in the exit port field is used to select a different destination. If the bit associated with a port 50 or 60 is set to 1, that port is selected to receive frame 187. Each LAN port 50 requires one associated bit in the exit port field 186. Each ATM port 60 requires two associated bits in the exit port field 186. Thus, the preferred embodiment, comprising three LAN ports 50 requiring one bit each and one ATM port 60 requiring two bits, uses five bits exit port field 186. Other LAN switch 20 embodiments having more ports 50 and 60 using more bits in exit port field 186.

Referring now back to FIGS. 4 and 5, the next step sends the LAN/switch frame through switch 70 to ATM port 60 as shown by block 210. The ATM ports sort incoming LAN messages to determine if they are to be routed or bridged as shown by block 212. The route verses bridge decision is based on the 2 exit ports assigned to ATM ports in switch header 180. Frames sent to the first exit port are routed, and frames sent to the second exit port are bridged. Routed frames require layer 3 format conversion and bridged frames require layer 2 format conversion.

Referring to FIG. 7, a block diagram is shown with further details of LAN frame sorting logic 80 of FIG. 4. Block 80 receives the incoming LAN frame 188 as it arrives from switch 70 over switch bus 52. The incoming frame 188 is temporarily buffered in IN frame data FIFO (First-In, First Out) buffer 302. Block 212 of FIG. 5

PATENT APPLICATION

shows the first flow decision at the ATM port 60 to be a checking of the exit port field 186 of switch header 180 to determine if the frame is routed or bridged. The IN decision block 304 of FIG. 7 makes and stores the routed verses bridged decision.

5

Routed frames require layer 3 data link protocol conversion, which is more complex than layer 2 conversion. Routing processor 130 (shown in FIG. 4) is used to process routed frames. Blocks 214 and 216 of FIG. 5 show a truncated flow path for routed frames. Block 306 of FIG. 7 sends the routed frames to the tail of software transmit queue 104, from which they are read by processor 130. The routed frames are converted using standard software procedures and are not pertinent to the present invention. Therefore, the flow of routed frames is not followed in FIG. 5.

10

15

20

25

Bridged frames require only layer 2 data link protocol conversion, and special-purpose hardware means are implemented in the switch-to-header conversion block 85 (shown in FIG. 4) to convert bridged frames quickly and efficiently without requiring processor intervention. Bridged frames are stored to hardware transmit queue 102, from which frame 188 is read to block 85 of FIG. 4, as shown by block 220 of FIG. 5. The storing of the incoming frame 188 to queue 102 is controlled by block 306, which places the frame at the tail of queue 102. There are four queues 102, 104, 202, 204 shown in FIG. 4 that are mapped as FIFOs into frame memory 100 of FIG. 7 and FIG. 4. Each queue stores multiple frames and has a head and a tail. Frames are added to the tail of queue 102 by block 306, which keeps track of the frame memory 100 address where the tail of the queue is located. Bridged frames are

PATENT APPLICATION

taken from the head of queue 102 and processed by block 85, which keeps track of the frame memory 100 address where the head of the queue is located.

5 Blocks 220 and 222 of FIG. 5 show the next steps of reading each frame from frame memory 100, in turn, from the head of queue 102 and then performing the hardware format conversion and forwarding. The queues 102, 104, 202, 204 provide buffering to smooth the transfer rates from the LAN to ATM and ATM to LAN. The
10 frame is read from frame memory 100 under the control of block 310 of FIG. 8. The switch header 180 is sent to hardware format converter block 312. Block 312 uses the tag field as an address to conversion tables 110 in frame memory 100 of FIG. 4 and accesses directly from table 110 the information required to convert
15 formats. The format conversion involves replacing the switch header 180 of frame 188 with ATM control header 280, which is shown in FIG. 9. The switch header 180 is stripped in its entirety from frame 187 and ATM control header 280 is added to make an ATM frame 288. The ATM frame 288, shown in FIG. 9, is comprised of the LAN
20 frame 287 as received from LAN 30 into LAN port 50 prefixed with ATM control header 280.

Referring to FIG. 9, ATM control header 280 is comprised of
virtual channel connection (VCC) field 282 for defining the
25 transmission channel when sending the frame through the ATM network, unused field 284, and LAN emulation header 286. The use of the LAN emulation header 286 will be discussed in detail hereinafter.

PATENT APPLICATION

Referring back to FIG. 8, hardware format converter 312, after addressing tables 110 destroys switch header 180, reads ATM control header 280 from tables 110, and stores ATM control header 280 until it is needed. Block 310 informs ATM enqueue logic 314 that a LAN frame conversion to the ATM frame format 288 is ready to send to the ATM adapter 120. Referring to FIG. 10A, a simplified diagram of ATM Adapter 120 shows the three major functional blocks of ATM Adapter 120: ATM memory 122, segmenter 124, and reassembler 126. ATM memory 122 stores a plurality of frames 288 to be transmitted to the ATM network 25. The ATM adapter 120 contains an ATM controller ASIC which segments/reassembles ATM cells for transmission to and from the ATM network. ATM memory 122 also stores a plurality of frames 288 which are being received from ATM network 25 and reassembled in reassembler 126. Segmenter 124 reads ATM frames from ATM memory 122 and segments them into 53-byte ATM cells for transmission to the ATM network 25.

The ATM cells 290 are comprised of five bytes of cell header 292 and 48 bytes of data 294, as shown in FIG. 10B. For the present invention the cell header 292 is created by segmenter 124 from VCC information field 282 of ATM controller header 280. The 48 data bytes 294 are also created by segmenter 124, which reads frame 288 from ATM memory 122 and sequentially includes 48 bytes per cell into sequential ATM cells 290 until the entire frame 288 including ATM control header 280 is transmitted over the ATM network 25. Reassembler 126 receives ATM cells 290 from ATM network 25, discards cell header 292, and reassembles data bytes 294 back into frames 288 in ATM memory 122. Note that ATM adapter 120 is prior art and described briefly herein to show the complete

data flow from LANs 30 to ATM network 25. The importance of ATM adapter 120 to the present invention is that it accepts LAN frames in the ATM frame format 288 and converts frames 288 to ATM cells 290 and receives ATM cells 290 and converts them to frames 288.

5

10

15

20

25

Referring to FIG. 8, when a buffer is available in ATM memory 122 of ATM adapter 120 to receive the frame 288, OUT frame DMA controller 316 transfers the ATM control header 280 from hardware format converter 312 to the buffer in ATM memory 122 and then controls the DMA transfer of the LAN frame 287 from frame memory 100 to ATM memory 122 such that frame 288 is formed in ATM memory 122 comprising LAN frame 287 prefixed with ATM control header 280. After the entire frame 288 has been transferred to ATM memory 122, ATM adapter enqueue logic 314 signals ATM adapter 120 that it can now transmit frame 288 to ATM network 25, thus completing the transmit operation. The operation flow diagram of FIG. 5 shows these last two steps of the operation in blocks 226 and 228.

Receiving ATM to LAN Frames

For receiving frames 288 from ATM port 60 to LAN port 50, frame 288 first arrives from ATM network 25 into ATM port 60 and is reassembled by reassembler 126 of ATM adapter 120 of FIG. 10A.

Reassembler 126 removes the cell header 292 from ATM cells 290 and collects only the data bytes. Frame 288 is reassembled in a buffer in ATM memory 122.

PATENT APPLICATION

Referring to FIG. 11, a flow diagram is shown of the receive operation. Block 400 starts the receive operation by reassembling frame 288 in ATM memory 120. When the entire frame 288 has been reassembled, ATM control header 280 is read from the ATM memory 120 to the received frame classification block 90. Referring to FIG. 12, a detailed functional diagram is shown of block 90 of FIG. 4. ATM control header 280 is examined by redirect frame logic 502 and ATM header classify logic 504 to determine if it is a bridged frame, a routed frame, or a LAN emulation control frame. Redirect frame logic 502 determines if the incoming frame 288 is a LAN emulation control frame. The details are discussed hereinafter. ATM header classify logic 504 makes the routed frame verses bridged frame decision based upon several bits of the VCC number. Routed frames are transferred to software receive queue 204 of frame memory 100, as shown in blocks 402 and 403 of FIG. 11. Note that the routed frame path is not pertinent to the present invention and its flow is not followed in FIG. 11. Erroneous frames are forwarded by blocks 404, 405, 407 and LAN emulation control frames are forwarded by blocks 404, 405, 406, 407. Like routed frames, erroneous and LAN emulation control frames are sent for software processing and are not pertinent paths of the present invention. Recognizing and classifying the LAN emulation control frame is part of the present invention, which is discussed further hereinafter.

The path of interest starts at block 408 of FIG. 11, where the ATM frame 288 is bridged to LAN port 50. Referring to FIG. 12 for bridged frames, IN frame DMA control logic 500 controls the transfer of the entire frame 288 from ATM memory 120 to hardware receive queue 202 of frame memory 100. Receive frame store control

logic 506 controls the storing of the received frame 288 to the tail of FIFO queue 202 to frame memory 100, and updates its pointers to point to the next tail value when the store is complete.

5

Referring to FIG. 4, bridged frames are taken from the head of the FIFO queue 202 and processed by ATM-to-switch header conversion block 95. FIG. 13 is a block diagram showing further details of the ATM-to-switch header conversion block 95. Receive frame read control logic 600 reads the ATM control header 280 from the head of hardware receive queue 202 and sends the header 280 to switch header look-up logic 602. Logic 602 maps the VCC number 282 of ATM control header 280 to a logical port number, also referred to as the virtual LAN (VLAN) number for VLAN filtering as shown in block 410 of FIG. 11. This is done by using VCC 282 to address conversion tables 110 in frame memory 100.

10

15

20

25

Referring to FIG. 14, the logical port conversion word 700 is read from conversion tables 110 as the first ATM-to-switch header conversion look-up. Word 700 is comprised of the logical port (VLAN) number 704. The VLAN number 704 and Destination MAC address of the LAN frame 287 are sent to the conversion tables 110 as the second ATM-to-switch header look-up to access the destination switch header 180, as shown by block 412 of FIG. 11. The second look-up table is called the filter table and the value accessed from the filter table determines if the LAN frame 287 can be forwarded or not, as shown by block 416 of FIG. 11. If the LAN frame 287 cannot be forwarded, the frame 288 is discarded as shown by block 418 of FIG. 11. This operation is called filtering.

Referring to FIG. 6 (switch header format) if the frame 288 is not filtered, LAN frame 287 is converted from having ATM control header 280 to having switch header 180, and the converted frame is sent through switch 70 to LAN port 50 for transmission to LAN 30. The switch header 180 is generated from the filter table look-up by using the VLAN number 704 to index into that portion of the filter table containing entries for the Destination MAC addresses in that VLAN. The exit port in switch header 180 defines either a unicast or multicast destination for the forwarded LAN frame 287. The switch header 180 is stored to switch header prefix logic 606, while LAN frame 287 without ATM control header 280 is read from frame memory 100 under the control of receive frame read control logic 600 to OUT frame FIFO 604. The LAN frame is assembled by first reading the switch header 180 from switch header prefix logic 606 to switch bus 52. Next LAN frame 287 follows switch header 180 immediately and is sent from OUT frame FIFO 604 to switch bus 52 to switch 70, as shown by block 414 of FIG. 11.

Virtual LANs and LAN Emulation

LAN emulation involves the integration of existing Ethernet and Token Ring LANs with ATM networks. LAN emulation is required because the current generation of LAN applications are not provided directly by ATM networks. LANs provide data delivery to a single destination or multiple destinations based on a destination MAC address. On the other hand, ATM networks are not compatible directly with LANs because ATM networks deliver data on virtual channel connections (VCCs) that must be set-up in advance. LAN emulation provides the conversion layer that handles the

PATENT APPLICATION

complexities of ATM connection set-up, so that it is transparent to LAN applications. Thus, the ATM network functions virtually like a LAN for interconnecting LANs and is called a virtual LAN (VLAN).

5 Referring to FIG. 4 for performing fast conversions of MAC addresses to VCC addresses and vice versa, conversion tables 110 are loaded into frame memory 100 in advance. Tables 110 change with the application and are continually updated. The present invention provides a method for changing the values that control
10 LAN emulation using LAN emulation header 286 of FIG. 9. The binary value which comprises the LAN emulation header 286, defines 8 LAN emulation control frames used to load values to ATM port 60 for controlling LAN emulation.

15 Referring to FIGS. 12 and 15, the LAN emulation (LAN E) hardware 800 internal to the redirect frame logic 502 implements eight 16-bit values stored in internal control registers 801 to 808. The LAN emulation header 286 for the received frame 288 is stored to register 810. Comparator 820 compares each register 801 to 808 to LAN emulation header 286 to determine if any of the
20 registers 801 to 808 compare equally to LAN emulation header 286. If there is no compare, the incoming frame 288 is handled by ATM header classify logic 504 as either a routed or a bridged frame as described hereinabove. If there is a match from comparator 820, a
25 LAN emulation control frame is detected which is forwarded to software receive queue 204 for further processing by the software. The software uses the information in the LAN emulation control frame to load the conversion tables, registers 801 and 808 and other miscellaneous LAN emulation control parameters. Note that

PATENT APPLICATION

registers 801 to 808 are loaded under software control and are not hardware forced to constant values.

It is an advantage of this invention to provide a high performance bridging path between dissimilar networks by implementing the bridging path as a hardware forwarding engine for transmitting LAN frames between LAN ports and ATM ports of the LAN switch.

It is a further advantage of this invention to sort incoming LAN messages at each port of the LAN switch into two different paths for efficient routing or bridging between dissimilar networks.

It is a further advantage of this invention to provide LAN emulation over ATM networks which permits LAN frames to be transmitted between two different LAN segments interconnected by an ATM network.

It is a further advantage of this invention to provide two different types of memory queues, one being a software queue of frames to be processed by a microprocessor and the other being a hardware queue of frames to be processed by a hardware forwarding engine.

It will be appreciated that, although a specific embodiment of the invention has been described herein for purposes of illustration, various modifications may be made without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A local area network (LAN) switching apparatus for interconnecting a LAN segment to an Asynchronous Transfer Mode (ATM) network, comprising:

a plurality of LAN ports, wherein each LAN port connects one unique LAN segment to a LAN switch;

at least one ATM port, wherein each ATM port of the LAN switch interfaces to the ATM network;

a connection means for establishing a plurality of connection paths simultaneously, wherein each said connection path establishes a connection through the switching apparatus between any two or more of the plurality of LAN ports and ATM ports, said connection path for transmitting data comprising LAN frames;

a data transmission means for formatting data for transmission over said LAN into standard LAN frames in compliance with the international standard of Open Systems Interconnection (OSI), wherein said standard provides a universally applicable layered architecture containing seven layers, numbered from 1 to 7, with each layer having a set of defined functions and providing a set of services to and from the adjacent two layers; and

a LAN to ATM format conversion means for changing the format of data as it traverses the LAN switch from LAN port to switch to ATM port, wherein LAN frames are converted to switch frames for transfer through the switching apparatus and switch frames are converted to ATM frames in preparation for transfer to the ATM network;

an ATM adapting apparatus for converting ATM frames to ATM network format and ATM network format to ATM frames, wherein ATM

PATENT APPLICATION

network format comprises segmenting said ATM frame into sequential ATM cells comprising 5 bytes of header and 48 bytes of data; and a first multiprotocol processing means, wherein said LAN switch converts either layer 2 or layer 3 of the OSI standard from LAN frames to switch frames to ATM frames, wherein LAN frames are compatible with LAN protocol and ATM frames are compatible with the first ATM adapting apparatus protocol.

2. The LAN switching apparatus of claim 1 further comprising:

an ATM to LAN format conversion means for changing the format of data as it traverses the LAN switch from ATM port to switch to LAN port, wherein ATM frames are converted to switch frames for transfer through the switching apparatus and switch frames are converted to LAN frames for transfer to the LAN port; and

a second multiprotocol processing means, wherein the LAN switch converts either the layer 2 or layer 3 of the OSI standard from ATM frames to switch frames to LAN frames.

3. The LAN switching apparatus of claim 2, further comprising a sorting means for the ATM port, wherein the ATM port sorts LAN frames arriving from said switch connection path and ATM frames arriving from the ATM network into three categories, comprising:

a first category of frames for routing, wherein layer 3 of the OSI standard is converted from LAN frames to ATM frames, or layer 3 of the OSI standard is converted from ATM frame format to LAN frame format;

a second category of frames for bridging, wherein layer 2 of the OSI standard is converted from LAN frame format to ATM frame

PATENT APPLICATION

11 format or layer 2 of the OSI standard is converted from ATM frame
12 format to LAN frame format; and
13 a third category of frames for aborting, wherein LAN frames or
14 ATM frames are erroneous and cannot be routed or bridged.

1 4. The LAN switching apparatus of claim 3 wherein the ATM port
2 further comprises a hardware forwarding means for bridging frames
3 from switch frame format to ATM frame format, or from ATM frame
4 format to switch frame format, said bridging without requiring
5 processor intervention.

1 5. The LAN switching apparatus of claim 4 wherein the ATM port
2 further comprises a routing processor means for routing switch
3 frames and routing ATM frames under software control.

1 6. The LAN switching apparatus of claim 5 wherein the sorting
2 means further comprises a single ported frame memory comprising:
3 a hardware transmit queue for temporarily storing switch
4 frames in transit between the switch and the ATM adapting apparatus
5 for subsequent accessing by the hardware forwarding means for
6 bridging switch frames to ATM frames;

7 a software transmit queue for temporarily storing switch
8 frames in transit between the switch and the ATM adapting apparatus
9 for subsequent accessing by the routing processor means for routing
10 under software control switch frames to ATM frames;

11 a hardware receive queue for temporarily storing ATM frames in
12 transit between the ATM adapting apparatus and the switch for
13 subsequent accessing by the hardware forwarding means for bridging
14 ATM frames to switch frames;

15 a software receive queue for temporarily storing ATM frames in
16 transit between the ATM adapting apparatus and the switch for
17 subsequent accessing by the routing processor means for routing
18 under software control ATM frames to switch frames; and

19 a set of conversion tables for assisting the hardware
20 forwarding means for converting switch frames to ATM frames and ATM
21 frames to switch frames.

1 7. The LAN switching apparatus of claim 6 wherein the sorting
2 means operates such that frames of the first category are stored to
3 the software transmit queue, frames of the second category are
4 stored to the hardware transmit queue, and frames of the third
5 category are discarded.

1 8. The LAN switching apparatus of claim 7 wherein the hardware
2 forwarding means further comprises an ATM formatting means for
3 generating an ATM frame format, comprising the LAN frame prefixed
4 with an ATM control header, the ATM control header comprising:

5 a virtual channel connection field for defining the connection
6 route through the ATM network; and

7 a LAN emulation header for identify unique LAN frames for
8 carrying control information.

1 9. The LAN hardware switching apparatus of claim 8 wherein the
2 hardware forwarding means further comprises a LAN formatting means
3 for generating a switch frame format, comprising the LAN frame
4 prefixed with a switch header, the switch header comprising:

5 a tag field for specifying the address of the conversion table
6 entry for access by the hardware forwarding means from the frame

PATENT APPLICATION

memory to obtain the conversion parameters to ATM frame format, comprising the virtual channel connection field and the LAN emulation header;

a frame type field for characteristics of the switch frame, and an exit port definition field for defining to the connection means which switch port is the destination of the switch frame.

10. The LAN switching apparatus of claim 9 wherein the hardware forwarding means further comprises a hardware format converter for converting switch frames to ATM frames by replacing the switch header with the ATM control header.

11. The LAN switching apparatus of claim 10 wherein the hardware forwarding means addresses the conversion tables in frame memory using the tag field of the switch header to access the ATM control header, whereupon the switch header is destroyed and the ATM control header is accessed from the conversion tables and prefixed to the LAN frame.

12. The LAN switching apparatus of claim 11, further comprising an ATM memory queuing means, wherein ATM frames are temporarily stored before being segmented and transmitted to the ATM network or after being received and reassembled from the ATM network.

13. The LAN switching apparatus of claim 9 wherein the hardware forwarding means further comprises ATM enqueueing means, wherein the ATM enqueueing means requests a queue from ATM memory queuing means, when the request is granted, sends the ATM frame to ATM memory queuing means from the hardware transmit queue in frame memory,

6 erases the ATM frame from hardware transmit queue, and signals ATM
7 adapting apparatus to segment and transmit the ATM frame.

1 14. The LAN switching apparatus of claim 13 wherein the sorting
2 means further comprises an exit port destination field of the
3 switch header including a first binary bit value for defining
4 frames to be routed and a second binary bit value for defining
5 frames to be bridged.

1 15. The LAN switching apparatus of claim 14 wherein the sorting
2 means sorts frames such that frames of the first category are
3 stored to the software receive queue, frames of the second category
4 are stored to the hardware receive queue, and frames of the third
5 category are discarded.

1 16. The LAN switching apparatus of claim 15 wherein the hardware
2 forwarding means further comprises a virtual LAN number for
3 identifying the ATM frame, wherein the virtual channel connection
4 field of the ATM control header is used to address the conversion
5 tables and access a virtual LAN number.

1 17. The LAN switching apparatus of claim 16 wherein the hardware
2 forwarding means further comprises a virtual LAN filtering means
3 for determining whether the ATM frame arriving from the ATM network
4 is to be bridged to the LAN or discarded.

1 18. The LAN switching apparatus of claim 17 wherein the virtual
2 LAN number and Destination MAC Address of the ATM frame is used to
3 address the conversion tables and access a valid or invalid

4 destination switch header, wherein frames having a valid
5 destination switch header are bridged and frames not having a valid
6 destination switch header are discarded.

1 19. The LAN switching apparatus of claim 18 wherein the hardware
2 forwarding means further comprises an ATM to switch conversion
3 means for converting ATM frames to switch frames by replacing the
4 ATM control header with the switch header.

1 20. The LAN switching apparatus of claim 19 wherein the said ATM
2 control header is destroyed and the switch header is generated from
3 the valid switch destination address and frame type field accessed
4 from conversion tables and the switch header is prefixed to the LAN
5 frame.

1 21. The LAN switching apparatus of claim 20 wherein the virtual
2 channel connection field of the ATM control header includes a first
3 binary value for defining frames to be routed and a second binary
4 value for defining frames to be bridged.

[illegible]

- 1
- 2
- 3

PATENT APPLICATION

1 24. A bridging apparatus comprised only of hardware for converting
2 and forwarding frames having a first frame format to frames having
3 a second frame format, said conversion without requiring processor
4 intervention.

1 25. The bridging apparatus of claim 24, further comprised of
2 conversion tables for assisting in said converting and forwarding
3 of frames.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
22

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

- 1
- 2
- 3
- 4

1 27. A LAN emulation system comprising:
2 a plurality a local area networks (LANs);
3 an ATM network;
4 a plurality of LAN switches for interconnecting LANs and ATM
5 networks;
6 a controlling processor; and
7 a LAN emulation means, wherein communications in the form of
8 frames are transmitted from a first LAN to the LAN switch to the
9 ATM network to the LAN switch to a second LAN.

1 28. The LAN emulation system of claim 27 wherein the LAN emulation
2 means further comprises LAN emulation control hardware for
3 presetting LAN switch controls in advance of the frame transmission
4 for controlling the ATM network to function like a LAN when
5 transporting frames from LANs to ATM or ATM to LANs.

1 29. The LAN emulation system of claim 28 wherein the LAN emulation
2 means further comprises a LAN emulation header means for
3 identifying frames having information for presetting the LAN
4 emulation control hardware.

1 30. The LAN emulation system of claim 29 wherein the LAN emulation
2 control hardware further comprises a plurality of registers for
3 storing LAN emulation headers, wherein each register contains a
4 unique LAN emulation header data pattern.

1 31. The LAN emulation system of claim 30 wherein the plurality of
2 registers specify the set of LAN emulation headers that contain
3 information for presetting the LAN emulation control hardware.

PATENT APPLICATION

1 32. The LAN emulation system of claim 30 wherein the LAN emulation
2 means further comprises a LAN emulation control sorting means for
3 checking each LAN emulation header arriving from the ATM network to
4 determine if the LAN emulation header matches any of the prestored
5 plurality of LAN emulation headers in the registers and contains
6 information for presetting the LAN emulation control hardware.

1 33. The LAN emulation system of claim 32 wherein the LAN emulation
2 means further comprises a forwarding means, wherein frames arriving
3 from the ATM network containing information for presetting the LAN
4 emulation control hardware are sent to the controlling processor to
be processed.

PATENT APPLICATION

METHOD AND APPARATUS FOR HARDWARE FORWARDING OF LAN FRAMES OVER ATM NETWORKS

ABSTRACT

5

10

A multiported LAN switch comprised of legacy local area network ports and ATM ports. Each ATM port comprising a hardware forwarding engine for bridging LAN frames from the LAN ports to the ATM port. The hardware forwarding engine converts layer 2 protocols between the dissimilar ports expediently, without requiring intervention by a microprocessor. A substantial performance gain is attained compared to microprocessor controlled format converters. Both LAN emulation and virtual LANs are supported.

7	APPLICATION LAYER	PROVIDES A MEANS FOR APPLICATION PROCESS TO COMMUNICATE WITH ONE ANOTHER THROUGH THE OSI SYSTEM. CONTAINS MANAGEMENT FUNCTIONS TO SUPPORT DISTRIBUTED APPLICATIONS.
6	PRESENTATION LAYER	PROVIDES REPRESENTATION OF INFOR- MATION TO APPLICATION LAYERS IN A WAY THAT PRESERVES THE MEANING WHILE RESOLVING ANY DIFFERENCES IN FORMAT AND DATA REPRESENTATION BETWEEN THE APPLICATION SYSTEMS.
5	SESSION LAYER	PROVIDES THE MEANS NECESSARY TO COORDINATE DIALOGUE BETWEEN PRESENTATION ENTITIES.
4	TRANSPORT LAYER	PROVIDE END-TO-END CONTROL TO ALLOW FOR ERROR RECOVERY AND DETECTION TO THE HIGHER LAYERS.
3	NETWORK LAYER	ESTABLISHES, MAINTAINS, AND TERMI- NATES NETWORK CONNECTIONS BETWEEN END SYSTEMS. RESPONSIBLE FOR CONTROLLING THE FLOW OF DATA TO THE NETWORK.
2	LINK LAYER	PROVIDES SYNCHRONIZATION AND ERROR CONTROL FOR INFORMATION TRANSMITTED OVER THE PHYSICAL LINK.
1	PHYSICAL LAYER	PROVIDES ELECTRICAL, MECHANICAL, FUNCTIONAL, AND PROCEDURAL CHARACTERISTICS REQUIRED FOR THE PHYSICAL LINK.

FIG. 1 (PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 9




FIG. 8




FIG. 10B




FIG. 10A

RA9-97-043
9/12




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

**Declaration and Power of Attorney for
Patent Application**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Method and Apparatus for Hardware Forwarding of
LAN Frames Over ATM Networks

the specification of which (check one)



is attached hereto.



was filed on _____ as Application Serial No. _____

_____ and was amended on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

Number	Country	Day/Month/Year	Priority Claimed
--------	---------	----------------	------------------

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Prior U.S. Applications:

Serial No.	Filing Date	Status
------------	-------------	--------

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Thomas F. Galvin, Reg. No. 25,394; Joscelyn G. Cockburn, Reg. No. 27,069; Gerald R. Woods, Reg. No. 24,144; John J. Timar, Reg. No. 32,497; John D. Flynn, Reg. No. 35,137, Michele A. Mobley, Reg. No. 35,616.

Send all correspondence to: John J. Timar, 972/B656, IBM Corp., PO Box 12195, Res. Tri. Park, NC 27709

-
- (1) Inventor: Dennis Albert Doidge
Signature: *Dennis Albert Doidge* 10/20/97
Residence: 106 Park Canyon Lane
Apex, NC 27502
Citizenship: USA
Post Office Address: Same
- (2) Inventor: Jim P. Ervin
Signature: *Jim P. Ervin* 10/21/97
Residence: 11804 Canonero Place
Raleigh, NC 27613
Citizenship: USA
Post Office Address: Same
- (3) Inventor: Douglas Ray Henderson
Signature: *Douglas R. Henderson* 10/21/97
Residence: 7300 Quinby Court
Raleigh, NC 27613
Citizenship: USA
Post Office Address: Same
- (4) Inventor: Edward Hau-chun Ku
Signature: *Edward Hau-chun Ku* 10/20/97
Residence: 115 Lochwood West
Cary, NC 27511
Citizenship: USA
Post Office Address: Same

(5) Inventor: Pramod Narottambhai Patel

Signature: Pramod Narottambhai Patel 10/20/97
Date

Residence: 124 Haddonfield Lane
Cary, NC 27513

Citizenship: USA

Post Office
Address: Same

(6) Inventor: Loren Blair Reiss

Signature: Loren Blair Reiss 10/21/97
Date

Residence: 308 Northclift Drive
Raleigh, NC 27609

Citizenship: USA

Post Office
Address: Same

(7) Inventor: Thomas Eric Ryle

Signature: Thomas Eric Ryle 10/20/97
Date

Residence: 9533 Bells Valley Drive
Raleigh, NC 27613

Citizenship: USA

Post Office
Address: Same

(8) Inventor: Joseph M. Rash

Signature: Joseph M. Rash 10/20/97 Date

Residence: 1628 Great Woods Road
Wake Forest, NC 27587

Citizenship: USA

Post Office
Address: Same